

## ABSTRACT OF THE INVENTION

A method and apparatus are used in accordance with the present invention in concurrent program analysis for detecting potential race conditions such as data races in computer programs. A feature of the method and apparatus of the present invention is verifying

5 annotations of addressable resources in a program. The present invention verifies annotations by checking if thread-local resources are indeed thread-local, and that thread-shared data

spaces are not in fact thread-local. In accordance with the purpose of the invention, the method provides for detecting potential race conditions, such as data races, in a computer

10 program. The computer program can spawn a plurality of threads that are capable of being executed concurrently. The method includes receiving a source code of the computer

program. The source code includes an element annotated as either thread-local or thread-

shared. The method also includes verifying the validity of the thread-local annotation if the

element is annotated in the computer program as thread-local, wherein an invalid thread-local annotation may cause a race condition. The method can further include indicating a potential

5 race condition if upon verifying the validity of the thread-local annotation it is determined that the element or a portion thereof is visible from more than one, rather than one and only

one, of the plurality of threads. In further accordance with the purpose of the invention, the apparatus for concurrent program analysis includes means for receiving source code of the

computer program. The source code includes an element annotated as either thread-local or

20 thread-shared. The apparatus also includes means for type checking the source code; and

means for thread-local checking located either inside or in series with the type checking

means. The means for thread-local checking includes means for verifying the validity of the

thread-local annotation if the element is annotated in the computer program as thread-local,

where an invalid thread-local annotation may cause a race condition such as a data race. The

25 apparatus can further include means for parsing the source code; and means for creating from

the source code an abstract syntax tree. Accordingly, the present invention beneficially

provides for a more effective concurrent program analysis.